

Made for your enterprise. Built for performance.

Every business needs a reliable business partner. The new mono laser series helps you maximise print efficiency and minimise costs so you can make the most of your investment.



HL-L6200DW


HL-L6200DW

	HL-L6200DW
Key Functions	Automatic 2-sided Print and Wireless Connectivity
PRINT FUNCTIONS	
Print Speed (A4/Letter)	Up to 50 / 52 ppm*
Print Resolution	Up to 1200 x 1200 dpi
First Print Out Time (Ready)	Less than 7.5 secs
Double-sided Feature	Automatic 2-sided Print
Special Print Functions	N-in-1 Printing, Poster Printing (Windows® only), Watermark Printing (Windows® only) Header-Footer Printing (Windows® only), Secure Print
Print Language	PCL6, BR-Script3, IBM Proprinter XL, Epson FX-850, PDF Version 1.7, XPS Version 1.0
Quiet Mode	Yes
PAPER HANDLING	
Input Tray (Standard)	520 Sheets
Multi-Purpose Tray / Manual Slot	50 Sheets 60-200g/m² (Paper weight) 76.2 to 215.9 mm (W) X 127 to 355.6 mm (L) (Paper size)
Output Tray (Face Down)	150 Sheets
Optional Paper Tray (Input)	250 sheets (LT-5500) or 520 sheets (LT-6500) x 2 pcs or 250 sheets x 3 pcs (Max. 1,040 sheets)
Media Size (Standard Tray)	A4, Letter, A5, A5 (Long Edge), A6, Executive, Legal, Folio, Mexico Legal, India Legal
OTHERS	
Memory	1GB
Processor Speed	Cortex-A9 (800MHz)
Duty Cycle	1,00,000
Display	16 characters x 1 line
Windows® (Host-Based)	Windows XP Home Edition, XP Professional Edition, XP Professional x64 Edition, Server 2003, Server 2003 x64 Edition, Vista, Server 2008, Server 2008 R2, 7, 8, 8.1, 10, Server 2012, Server 2012 R2
Apple Mac®	Mac OS X v10.8.5, 10.9.x, 10.10.x (Download only)
Linux® (Linux® Printer Driver)	CUPS, LPD/LPRng (x86/x64 environment)
Universal Printer Driver	Yes (BRScript / PCL)
Connectivity / Networking	Built-in Wireless 802.11b/g/n, Wi-Fi Direct, Built-in Gigabit Ethernet 10Base-T / 100Base-TX / 1000Base-T, Hi-Speed 2.0
Power Consumption (Sleep/Ready)	6.5W/32W
Power Source	220-240V, AC 50/60Hz
SUPPLIES	
Standard-Yield Toner	TN-3428: Approximately 3,000 pages**
High-Yield Toner	TN-3448: Approximately 8,000 pages**
Super High-Yield Toner	TN-3478: Approximately 12,000 pages**
Drum	DR-3455: Approximately 30,000 pages**
DIMENSIONS & WEIGHT	
Dimension (W X D X H)	373 x 388 x 287 mm
Weight	12.4kg

^{*} In accordance with ISO/IEC 11160-2:1996











Brother strongly recommends the use of genuine Brother consumable products only. Benefits include better quality print, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please note that your machine warranty may not cover any damages arising from the use of non-genuine consumables.



Microsoft, Windows, the Windows logo and/or other Microsoft products referenced herein are either registered trademarks of Microsoft Corporation in the U.S. and/or other countries. Brother and its logo are trademarks of Brother industries Ltd., Japan. All specifications are subject to change without notice. All registered trademarks referenced herein are the property of their respective companies.

^{**} In accordance with ISO/IEC 19752