## **ADS-4300N**





# Capture. Optimise. Collaborate.

# **Desktop** Document Scanner



www.brother.in

### **Specification**



#### General

**Product Form Factor** Sheet Fed Desktop Document Scanner

Scanner Type Dual CIS (contact Image Sensor), LED Array Light Source

**Control Panel** LED, 7 Keys (4 + 3 configurable shortcut keys for quick access) Backup Clock Up to 24 hours

**Local Interface** SuperSpeed USB 3.0, USB 2.0 Host (Rear)

#### Wired Network Interface

Wired Network interface (10Base-T/100Base-TX)

#### Mobile Scan

View scans on your mobile device from your Brother scanner

Scan

Scan Speeds (A4) (Colour & Mono) Up to 40 (pages per minute)

Scan Speeds 2-sided (A4) Up to 80 (images per minute)

**Optical Scan Resolution** Up to 600 x 600dpi (dots per inch) Interpolated Scan Resolution<sup>3</sup> Up to 1,200 x 1,200dpi (dots per inch)

**Wake-up Time** USB connected, approx 5 sec from sleep mode **Colour Depth** 48-bit internal 24-bit external

**Grey Scale** 256 levels (8 bit)

Plastic Card Mode.

Single Page Scan<sup>5</sup>,

Continuous Scan<sup>5</sup>,

Multi Feed Detection,

**Custom TWAIN Profiles** 

Ultra Sonic Multi Feed Sensor,

Barcode Detection<sup>5</sup>

Feed Control

Separation Switch

Scanner Functions Image Processing<sup>3</sup> Auto Deskew(Feed)<sup>7</sup>, Auto Image Rotation Auto Colour Detect Adjust, Blank Page Removal<sup>6</sup>,

File Format Support

Including PDF (single, multi, PDF/A-1b, secured, signed), JPEG, TIFF (single, multi)

Auto Scan Size, Scan Margin

Standard Functions Scan to PC, Image<sup>3</sup>, Network (SMB), FTP/SFTP Background Processing<sup>5</sup>, Colour Drop<sup>5</sup> Remove Ruled Line, 2in1 Scan, 1to2 Scan, Carrier Sheet Mode

**Scan Profiles**<sup>6</sup> Create up to 25 preset scan to SFTP/FTP/Network profiles

**Direct Scan** Scan directly to a USB (acceptable memory size upto 128GB)

Macintosh Software

Brother iPrint&Scan for Desktop, Remote Setup

Linux Drivers SANE

#### Software<sup>2</sup>

#### Windows Drivers<sup>7,8</sup>

TWAIN, ISIS, WIA Windows 10 (Home|Pro|Education|Enterprise) (32 or 64 bit editions), Windows 8.1(32 or 64 bit editions), Windows 7 SP1 (32 or 64 bit editions), Windows Server 2019, 2016, 2012R2, 2012

#### Windows Software

Brother ScanEssentials, Brother iPrint&Scan for Desktop, Kofax PaperPort, Kofax Power PDF Standard v3, Remote Setup

#### **Macintosh Drivers**

AirPrint Scan Support, TWAIN, macOS 10.14.x or greater

### **Specification**



#### Media Handling

Automatic Document Feeder (ADF) 80 Sheet<sup>4</sup>

**Media Sizes**<sup>11,12</sup> Width 50.8 - 215.9mm, Height 50.8 - 355.6mm, Long Paper 5000mm Plastic Card Length (ISO) - 85.60mm, Width (ISO) - 53.98mm

**Media Types** Plain Paper, Thin Paper, Thick Paper, Thicker Paper, Recycled Paper, Business Card, Plastic Card

#### Media

Paper Weight 40 - 200gsm Plastic Card Thickness Up to 1.32mm embossed, Up to 1.10mm without emboss

#### Mobile and Web Connectivity

**Brother Mobile Connect** Use a Brother app to scan to a mobile device running iOS or Android operating system

Fleet Management Tools

#### Embedded Web Server

Using the IP address or node name of your device access via a web browser to the web based print management software embedded onto the device using an encrypted password

#### LAN/WAN Management Software<sup>2,5</sup>

Brother BRAdmin Light and BRAdmin Professional 4

#### **Network Security**

IPv4

DHCP, APIPA (Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, SNMPv1/v2c/v3, ICMP, Web Services(Scan), HTTP/HTTPS server, LLMNR responder, SNTP Client

#### IPv6

RA, DNS Resolver, mDNS, LLMNR responder, Web Services(Scan), SNTP Client, HTTP/HTTPS server, ICMPv6

#### **IP Filter**

Restrict which network users can or cannot access the device over the network (IPv4 only)

#### Wired Network Security

SMTP-AUTH, SSL/TLS (HTTPS, SMTP), SNMP v3, 802.1x (EAP-FAST, PEAP, EAP-TLS, EAP-TTLS)

## Consumables & Upgrades

#### Carton Contents

ADS machine, detachable ADF. Power supply cord. AC adapter. USB Cable. Quick setup guide. Product safety guide. Warranty **Optional Roller Kit** PRK-A3001

Dimensions & Weights Scanner With Carton (WxDxH) 391 x 243 x 320 mm - 3.32kg Scanner Without Carton (WxDxH) 300 x 216 x 190 mm - 2.64kg

## **Specification**



**Duty Cycle** 

**Maximum Daily** 6.000 Sheets

#### **Environment**

**Power Requirements** AC: 100-240V, 50/60 Hz, DC: 24V, 1.9A

#### **Power Consumption**

Scanning 24W Ready 6.8W Sleep 1.7W Network Standby 2.1W Power Off 0.1W

**Power Saving Modes** Sleep, Power Down Auto Power On after power outage

**Sound Power** Scanning <59dB

**Operating Environment** Humidity 20 - 80 % 5°C - 35°C, 41°F - 95°F

**Storage Environment** Humidity 10 - 90 % -20°C to 60°C, -4°F to 140°F

- Maximum number of scanned pages per month can be used to compare design durability between like Brother products. 1
- For maximum scanner life, it is best to choose a scanner with a duty cycle that far exceeds your scan requirements
- Free download from the Brother Solutions Centre http://solutions.brother.com 2
- 3 All supported using downloadable software
- 4 Capacity varies dependent on paper weight
- 5 Windows Only
- Windows & macOS Only 6
- 7 Windows server support scanner driver only
- 8 Win7 / Server2008 SP2/R2 Extended Security Update (ESU) legacy support until 10/01/2023
- 9 Requires an Internet connection
- 10 Requires additional activation
- 11 Document sizes larger than A4, but not exceeding A3, can be scanned (single-side) using carrier sheet
- 12 Can scan documents longer than A4 size. When using Brother(TWAIN, ISIS) to scan at 200dpi, the maximum scanning length is 5,000mm



#### Brother International (India) Pvt. Ltd.

801 & 802, 8th Floor, Alpha Building, Hiranandani Gardens, Powai, Mumbai - 400076 🖀 : +91-22-66708900 | 🖶 : +91-22-6670899 | 💌 : customercare@brother.in | ⊕: www.brother.in Toll Free No.:1-800-222-422 (MTNL & BSNL users) & 1-800-209-8904 (All Other) Operating Hours: Mon to Fri (8:30am - 6:30pm) & Sat (9:00am - 6:00pm) Brother Showroom: Bangalore | Chennai | Delhi | Kolkata | Pune | Lucknow





7045 450 450